

**Electro-Voice EVF1152D/43PIW Premium 15 inch 2-Way Full-Range Loudspeaker/40x30deg/Evcoat/Weatherized/White**

Frequency Range (-10 dB)	40 - 21000kHz
Weight Net	34.4kg (75.84 lbs)
Depth	466.6mm (18.37")
Width	469.8mm (18.5")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB) H	40°
Coverage (Nominal -6 dB) V	30°
Crossover Frequency	1300Hz
Enclosure Material	13-ply weather-resistant birch with EVCoat
Environmental Specs	Standard versions: IEC 60529 IP44, PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	70 - 18000kHz
Grille	16 GA powder-coated galvalume with screen behind
HF Transducer	DH7N 3-inch (76mm) diaphragm compression driver
Input Connections	Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover
LF Nominal Impedance	8Ω
LF Transducer	DVX315A 15-inch (381 mm) woofer
Max. SPL/1m (calc)	134dB
Minimum Impedance	6Ω
Nominal Impedance (Passive)	8Ω
Passive Power Handling	2400W peak
Recommended High-Pass Frequency	45Hz
Sensitivity 1 W/1 m	100dB
Shipping Weight	39.1kg (86.2 lbs)
Speaker Type	Full-Range, Two-Way
Suspension	(22) M10 threaded suspension points
System Power Handling (Continuous/Program/Peak)	600/1200/2400 Watts
Weatherized	No