

Electro-Voice EVF1152S/43BLK 15 inch 2-Way Full-Range Loudspeaker/SMX Woofer/ND2B Driver/45x30deg/Evcoat/Black

Frequency Range (-10 dB)	41 - 18000kHz
Weight Net	32.1kg (70.77 lbs)
Depth	466.6mm (18.37")
Width	469.8mm (18.5")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB) H	40°
Coverage (Nominal -6 dB) V	30°
Crossover Frequency	1450Hz
Enclosure Material	13 Ply Weather Resistant Birch
Environmental Specs	Standard versions: IEC 60529 IP44
Frequency Response (-3 dB)	70 - 14000kHz
Grille	Standard versions: 16 GA Galvanneal, Powdercoat, with screen behind
HF Transducer	ND2B, 2 in (51 mm) Diaphragm Compression Driver
Input Connections	Phoenix/Euroblock style screw terminals
LF Transducer	SMX2151, 15 in (381mm) Driver
Max. SPL/1m (calc)	134dB
Minimum Impedance	6Ω
Nominal Impedance (Passive)	8Ω
Passive Power Handling	2000W peak
Recommended High-Pass Frequency	45Hz
Sensitivity 1 W/1 m	101dB
Speaker Type	Full-Range, Two-Way
Suspension	(22) M10 Threaded Points
System Power Handling (Continuous/Program/Peak)	500/1000/2000Watts
Weatherized	No