

**Electro-Voice EVF1152S/99FGW 15 inch 2-Way Full-Range Loudspeaker/SMX Woofer/ND2B Driver/90x90deg/Fiberglass/White**

|   |  |
|---|--|
| Frequency Range (-10 dB)                        | 41 - 18000kHz  |
| Weight Net                                      | 32.1kg (70.77 lbs)   |
| Depth   | 466.6mm (18.37")   |
| Width   | 469.8mm (18.5")  |
| Height  | 768.6mm (30.26")   |
| Coverage (Nominal -6 dB) H                      | 90°  |
| Coverage (Nominal -6 dB) V                      | 90°  |
| Crossover Frequency                             | 1450Hz   |
| Enclosure Material                              | 13 Ply Weather Resistant Birch                                       |
| Environmental Specs                             | Standard versions: IEC 60529 IP44                                    |
| Frequency Response (-3 dB)                      | 70 - 14000kHz  |
| Grille  | Standard versions: 16 GA Galvanneal, Powdercoat, with Rotatable Logo |
| HF Transducer                                   | ND2B, 2 in (51 mm) Diaphragm Compression Driver                      |
| Input Connections                               | Phoenix/Euroblock style screw terminals                              |
| LF Transducer                                   | SMX2151, 15 in (381mm) Driver  |
| Max. SPL/1m (calc)                              | 134dB  |
| Minimum Impedance                               | 6Ω   |
| Nominal Impedance (Passive)                     | 8Ω   |
| Passive Power Handling                          | 2000W peak   |
| Recommended High-Pass Frequency                 | 45Hz   |
| Sensitivity 1 W/1 m                             | 101dB  |
| Speaker Type                                    | Full-Range, Two-Way  |
| Suspension                                      | (22) M10 Threaded Points   |
| System Power Handling (Continuous/Program/Peak) | 500/1000/2000Watts   |
| Weatherized                                     | No   |