

Electro-Voice EVF1181SWHT 18 inch 400W Front-Loaded Subwoofer/Bi-Amp Only/Evcoat/White

Frequency Range (-10 dB)	28 - 650kHz
Weight Net	45.9kg (101.19 lbs)
Depth	726.4mm (28.6")
Width	675.6mm (26.6")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB)	Omnidirectional in normal operating range
Coverage (Nominal -6 dB) H	360°
Enclosure Material	13 Ply Weather Resistant Birch
Environmental Specs	Standard versions: IEC 60529 IP44. PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	35 - 100kHz
Grille	Standard versions: 16-ga Galvanneal, Powdercoat, with screen behind. PI and FG versions: 18-ga Stainless, Powdercoat, with hydrophobic cloth behind
Input Connections	Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover
LF Transducer	EVS18SB, 18 in (457mm) Driver
Max. SPL/1m (calc)	131dB
Minimum Impedance	Passive: N/A, Bi-amp: 6Ω (Biamp)
Nominal Impedance	Passive: N/A, Bi-amp: 8Ω (Biamp)
Passive Power Handling	1600W peak
Recommended High-Pass Frequency	33Hz
Sensitivity 1 W/1 m	99dB
Speaker Type	Subwoofer
Suspension	(28) M10 Threaded Points (one EBK-M10-EVI kit of four forged eyebolts included)
System Power Handling (Continuous/Program/Peak)	400, 800, 1600Watts
Weatherized	No