

Electro-Voice EVF2151DWHT Dual 15 inch Front-Loaded Subwoofer/Evcoat/White

Frequency Range (-10 dB)	30 - 3200kHz
Weight Net	53.1kg (117.07 lbs)
Depth	726.4mm (28.6")
Width	675.6mm (26.6")
Height	768.6mm (30.26")
Coverage (Nominal -6 dB)	Omnidirectional in normal operating range
Coverage (Nominal -6 dB) H	360°
Coverage (Nominal -6 dB) V	Omnidirectional°
Enclosure Material	13-ply weather-resistant birch with EVCoat
Environmental Specs	Standard versions: IEC 60529 IP44. PI and FG versions: IEC 60529 IP55
Frequency Response (-3 dB)	40 - 2600kHz
Grille	Standard versions: 16-ga Galvanneal, Powdercoat, with screen behind. PI and FG versions: 18-ga Stainless, Powdercoat, with hydrophobic cloth behind
Input Connections	Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover
LF Transducer	Two DVX3159A 15-inch (381 mm) drivers
Max. SPL/1m (calc)	137dB
Minimum Impedance	Passive: N/A, Bi-amp: 2.7Ω (Biamp)
Nominal Impedance	Passive: N/A, Bi-amp: 4Ω (Biamp)
Passive Power Handling	4000W peak
Recommended High-Pass Frequency	35Hz
Sensitivity 1 W/1 m	101dB
Speaker Type	Subwoofer
Suspension	(28) M10 Threaded Points (one EBK-M10-EVI kit of four forged eyebolts included)
System Power Handling (Continuous/Program/Peak)	1000/2000/4000Watts
Weatherized	No