

Electro-Voice EVF2151DFGB Dual 15 inch Front-Loaded Subwoofer/Fiberglass/Black

| | |
|---|---|
| Frequency Range (-10 dB) | 30 - 3200kHz |
| Weight Net | 53.1kg (117.07 lbs) |
| Depth | 726.4mm (28.6") |
| Width | 675.6mm (26.6") |
| Height | 768.6mm (30.26") |
| Coverage (Nominal -6 dB) | Omnidirectional in normal operating range |
| Coverage (Nominal -6 dB) H | 360° |
| Coverage (Nominal -6 dB) V | Omnidirectional° |
| Enclosure Material | 13-ply weather-resistant birch with EVCoat |
| Environmental Specs | Standard versions: IEC 60529 IP44. PI and FG versions: IEC 60529 IP55 |
| Frequency Response (-3 dB) | 40 - 2600kHz |
| Grille | Standard versions: 16-ga Galvanneal, Powdercoat, with screen behind. PI and FG versions: 18-ga Stainless, Powdercoat, with hydrophobic cloth behind |
| Input Connections | Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover |
| LF Transducer | Two DVX3159A 15-inch (381 mm) drivers |
| Max. SPL/1m (calc) | 137dB |
| Minimum Impedance | Passive: N/A, Bi-amp: 2.7Ω (Biamp) |
| Nominal Impedance | Passive: N/A, Bi-amp: 4Ω (Biamp) |
| Passive Power Handling | 4000W peak |
| Recommended High-Pass Frequency | 35Hz |
| Sensitivity 1 W/1 m | 101dB |
| Speaker Type | Subwoofer |
| Suspension | (28) M10 Threaded Points (one EBK-M10-EVI kit of four forged eyebolts included) |
| System Power Handling (Continuous/Program/Peak) | 1000/2000/4000Watts |
| Weatherized | No |