

## Electro-Voice 7110XC 30 Watt/8 Ohms Explosion Proof Driver/Hazardous Environment/Explosion Proof (UL Listed)

Frequency Response:	500 Hz - 4,000 Hz $\pm$ 5 dB (see Figure 2)
Power Handling, 8 Hours, 6-dB Crest Factor:	30 watts (500-5,000 Hz pink noise)
Impedance, 7110XC Nominal:	8 ohms
Impedance, 7110XC Minimum:	6.5 ohms (Cobreflex III horn)
Sound Pressure Level at 1 Meter, 1 Watt Input Averaged, Pink Noise Band-Limited from 500 to 5,000 Hz:	100 Hz
Voice Coil Diameter:	3.8 cm (1.5 in.)
Magnet Weight:	0.28 kg (0.63 lb)
Magnet Material:	Strontium ferrite
Flux Density:	1.1 Tesla
Construction:	Integral sintered bronze acoustic screen and heavy diecast aluminum case. Acrylic gun metal gray finish
Mechanical Construction of Driver:	1 3/8"-18 x 1/2"- long thread allows the 7110XC to be mounted on any University Sound horn
Recommended Horns:	Cobreflex IIB / Cobreflex III
Dimensions:	
Diameter:	2.0 cm (7.9 in.)
Length:	18.7 cm (7.4 in.)
Net Weight:	5.4 kg (12.0 lb)
Shipping Weight:	5.6 kg (12.8 lb)