

Electro-Voice FRI28LPMBLK FRI Series Dual 8 inch 200W RMS/800W Peak 2-Way Speaker (Black/No Bracket)

Frequency Range (-10 dB)	55 - 16000kHz
Weight Net	18.2kg (40.12 lbs)
Depth	356mm (14.02")
Width	620mm (24.41")
Height	222mm (8.74")
Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	93dB
Chassis Size	203.2mm (8")
Coverage (Nominal -6 dB) H	100° (Const.-dir. horn)
Coverage (Nominal -6 dB) V	100° (Const.-dir. horn)
Crossover Frequency	2800Hz
Enclosure Material	13-ply Plywood
Flying	Included
Frequency Response (-3 dB)	70 - 20000kHz
HF Power Handling	200Watts
HF Transducer	1-inch (25 mm) compression driver
Input Connections	Barrier Strip (Single)
Internal Crossover	Yes
LF Transducer	Two 8-inch (203 mm)
Max. SPL/1m (calc)	122dB
Nominal Impedance (Passive)	8Ω
Passive Power Handling	800W peak
Power Rating	800W
Recommended High-Pass Frequency	50Hz (12 dB/octave)
Sensitivity 1 W/1 m	93dB
Speaker Type	Full-Range, Wedges
System Power Handling (Continuous/Program/Peak)	200//800Watts (Biamp)
Weatherized	No