

Aten CE100 USB VGA Cat 5 Mini KVM Extender (Transmitter/Receiver) Kit

Function	CE100L	CE100R
Connectors		
Console Ports	N/A	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue)
KVM Ports	1 x USB Type B Female (White) 1 x HDB-15 Male (Blue)	N/A
Power	1 x DC Jack	1 x DC Jack
Unit To Unit	1 x RJ-45 Female (Black)	1 x RJ-45 Female (Black)
Switches	N/A	1 x Knob
LEDs		
Link	1 (Blue)	1 (Blue)
Power	1 (Green)	1 (Green)
Video	1920 x 1200 @ 60 Hz (30 m); 1280 x 1024 @ 60 Hz (100 m)	1920 x 1200 @ 60 Hz (30 m); 1280 x 1024 @ 60 Hz (100 m)
Power Consumption	DC5V, 0.5W	DC5V, 1.25W
Environmental		
Operating Temperature	0-50°C	0-50°C
Storage Temperature	-20-60°C	-20-60°C
Humidity	0-80% RH, Non-condensing	0-80% RH, Non-condensing
Physical Properties		
Housing	Metal	Metal
Weight	0.17 kg (0.37 lb)	0.17 kg (0.37 lb)
Dimensions (L x W x H)	9.10 x 5.74 x 2.40 cm (3.58 x 2.26 x 0.94 in.)	9.10 x 5.74 x 2.40 cm (3.58 x 2.26 x 0.94 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	