

Aten CE350 PS/2 VGA/Audio Cat 5 KVM Extender

Supported Operating Systems	Windows: 2000, 2003, 2008, XP, Vista, 7 Linux: Redhat 9.0 and up; SuSE 10, 11.1 and up; Debian 3.1, 4.0; Ubuntu 7.04, 7.10 UNIX: FreeBSD 5.5, 6.1, 6.2 Novell: Netware 6.0 and up
Housing Material	Metal
Console Connectors	Mouse: 1 x 6-pin Mini-DIN female on both local and remote Keyboard: 1 x 6-pin Mini-DIN female on both local and remote Monitor: 1 x VGA female on both local and remote
CPU Connectors	Keyboard, mouse, and monitor: 1 x SPHD-17 female on local Audio: 1 x 3.5 mm mini stereo jack Microphone: 1 x 3.5 mm mini stereo jack
Connectors	RS-232: 1 x D89 on both local and remote
Cable Connection	Input: 1 x RJ45 (remote) Output: 1 x RJ45 (Local)
LED Indicator	1 x on both local and remote
Switches	Port selection: 1 x pushbutton Picture compensation: 1 x pushbutton
Power	Voltage: 5.3VDC (local and remote) Amps: 700mA local, 1.3A remote
Power Consumption (max)	Local: 3.38W - 11.5 BTU Remote: 6.43W - 22 BTU
Operating Temperature & Humidity	32 - 122°F (0 - 50°C), RH 0 - 80% non- condensing
Storage Temperature	-4 - 140°F (-20 - 60°C)
Dimensions (W x H x D)	Local: 7.8 x 1.0 x 3.2" (19.8 x 2.5 x 8.1 cm) Remote: 7.8 x 1.0 x 3.2" (19.8 x 2.5 x 8.1 cm)
Weight	Transmitter: 17.28 oz (0.49 kg) Receiver: 16.93 oz (0.48 kg)