

Aten CE700A USB VGA Cat 5 KVM Extender

Supported Operating Systems	Windows: 2000, XP, Vista Linux: Redhat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 930 and up UNIX: FreeBSD 4.2 and up Novell: Netware 6.0 and up
Connections	Local: HDB-15 female USB Type A Female Keyboard USB Type A Female Mouse SPHD-15 female RJ-45 female Remote: HDB-15 female USB Type A Female Keyboard USB Type A female Mouse DB-9 for RS232 RJ-45 female
Buttons	Console selection: 1 x pushbutton
LED Indicators	Local: 1 x green (local unit) Remote: 1 x green (local and remote units) Link: 1 x green (remote unit)
Video Resolution	1920 x 1200 @ 60 Hz (100') 1600 x 1200 @ 60 Hz (300') 1280 x 1024 @ 60 Hz (500')
Emulation	Keyboard, mouse: USB
Operating Temperature & Humidity	32 - 122°F (0 - 50°C), RH 0 - 80% non- condensing
Storage Temperature	-4 - 140°F (-20 - 60°C)
Power Consumption	Local: 8 BTU/h Remote: 10 BTU/h
Housing Material	Metal
Dimensions (L x W x H)	Local: 4.9 x 3.2 x 0.9" (12.4 x 8.1 x 2.3 cm) Remote: 4.9 x 3.2 x 0.9" (12.4 x 8.1 x 2.3 cm)
Weight	Local: 11.29 oz (0.32 kg) Remote: 10.93 oz (0.31 kg)