

Aten CE750A USB VGA/Audio Cat 5 KVM Extender (Transmitter/Receiver) Set

Function	CE750AL	CE750AR
Connectors		
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink) 1 x DB-9 Female (Black) 1 x RJ-45 Female 1 x DC Jack	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink) 1 x DB-9 Male (Black) 1 x RJ-45 Female 1 x DC Jack
KVM Ports	1 x SPHD-15 Female (Yellow) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)	N/A
LEDs		
Local	1 (Green)	N/A
Remote	1 (Green)	1 (Green)
Link	N/A	1 (Green)
Picture Compensation	N/A	1 (Orange)
Pushbuttons		
Operating Mode Selection	1 x Pushbutton	N/A
Picture Compensation	N/A	2 x Pushbuttons
Emulation		
Keyboard / Mouse	USB	USB
Video	1920x1200@60Hz at 30m; 1600x1200@60Hz at 150m; 1280x1024@60Hz at 200m	1920x1200@60Hz at 30m; 1600x1200@60Hz at 150m; 1280x1024@60Hz at 200m
Power Consumption	DC5.3V/2.68W	DC5.3V/3.6W
Environmental		
Operating Temperature	0-50°C	0-50°C
Storage Temperature	-20-60°C	-20-60°C
Humidity	0-80% RH, Non-condensing	0-80% RH, Non-condensing
Physical Properties		
Housing	Metal	Metal
Weight	0.47 kg (1.04 lb)	0.47 kg (1.04 lb)
Dimensions (L x W x H)	20.20 x 8.63 x 2.50 cm (7.95 x 3.4 x 0.98 in.)	20.20 x 8.01 x 2.50 cm (7.95 x 3.15 x 0.98 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	