

## Aten CE770 USB VGA/Audio Cat 5 KVM Extender with Deskew

Supported Operating Systems	Windows: 2000, XP, Vista Linux: Redhat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 9.0 and up UNIX: FreeBSD 4.2 and up Novell: Netware 6.0 and up
Connections	Local: 1 x SPHD-17 Female for Keyboard, Mouse, Video Mini stereo jack female Speaker (green) Mini stereo jack female Mic (pink) RJ-45 female DB-9 for RS232 Remote: HDB- 15 female USB Type A Female Keyboard USB Type A female Mouse Mini stereo jack female Speaker (green) Mini stereo jack female Mic (pink) RJ-45 female DB-9 for RS232
Cable Distance	1000' max
LED Indicators	Local unit: 2 x green (local, remote Remote unit: 1 x blue, 1 x orange / green (link), 1 x red (remote)
Switches	Mode selection: 1 x pushbutton local Picture compensation: 1 x pushbutton remote Sensitivity: 1 x pushbutton remote
Emulation	Keyboard, mouse: USB
Video Resolution	1920 x 1200 @ 60Hz (300'), 1280 x 1024 @ 60Hz (900')
Operating Temperature & Humidity	32 - 122°F (0 - 50°C), RH 0 - 80% non-condensing
Storage Temperature	-4 - 140°F (-20 - 60°C)
Power Consumption	Local: 3.5 W / 12 BTU/h Remote: 5.1 W / 17.4 BTU/h
Housing Material	Metal
Dimensions (W x L x H)	Local: 7.9 x 3.1 x 1.0" (20.0 x 8.0 x 2.5 cm) Remote: 7.9 x 3.1 x 1.0" (20.0 x 8.0 x 2.5 cm)
Weight	Local: 17.3 oz (0.49 kg) Remote: 17.3 oz (0.49 kg)