

## Aten CE775 USB VGA Dual View Cat 5 KVM Extender with Deskew

Supported Operating Systems	Windows: 2000, XP, Vista, 7 Linux: Redhat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 9.0 and up UNIX: FreeBSD 4.2 and up; Sun Solaris 8 and up Novell: Netware 6.0 and up Mac: OS 9 and up
Connectors	Console Ports (local and remote): Keyboard - 1 x USB type A female (white) Video - 2 x HDB-15 female (blue) Mouse - 1 x USB type A female (white) Speakers - 1 x mini stereo jack female (green) Mic - 1 x mini stereo jack female (pink) Main - 1 x RJ-45 female (black) Sub - 1 x RJ-45 female (black) KVM Ports (local only): Keyboard / video / mouse: 1 x SPHD-17 female (yellow) Speakers - 1 x mini stereo jack (green) Mic - 1 x mini stereo jack (pink) VGA input - 1 x HDB-15 male (blue) RS-232 (local and remote): 1 x DB-9 female (black) Power: 1 x DC jack (black)
Buttons or Switches	Operating mode selection (local and remote): 1 x pushbutton Wakeup computer (remote only): 1 x pushbutton Video output port selection (remote only): 1 x slide switch Video gain tuner (remote only): 1 x knob Video compensation tuner (remote only): 1 x knob RGB tuner: 3 x knob (remote only)
LED Indicators	Local unit: 2 x green (local, remote) Remote unit: 1 green (link)
Emulation	Keyboard, mouse: USB
Video Resolution	1920 x 1200 @ 60Hz (500' (150 m)), 1280 x 1024 @ 60Hz (1000' (300 m))
Operating Temperature & Humidity	32 - 122°F (0 - 50°C), RH 0 - 80% non-condensing
Storage Temperature	-4 - 140°F (-20 - 60°C)
Power Consumption	Local: 5.3 VDC / 4.38 W Remote: 5.3 VDC / 10.27 W
Housing Material	Metal
Dimensions (W x L x H)	Local: 7.9 x 3.0 x 1.7" (20.0 x 7.6 x 4.2 cm) Remote: 7.9 x 3.0 x 1.7" (20.0 x 7.6 x 4.2 cm)
Weight	Local: 1.52 lb (0.69 kg) Remote: 1.52 lb (0.69 kg)