

## Aten CL1308N 8-Port 19 ft LCD Integrated USB/PS2 Combo KVM Switcher

Computer Connections	Direct	8	
	Maximum	128 (via Cascade)	
Port Selection	OSD, Hotkeys, Pushbuttons		
Connectors	KVM Ports	8 x SPHD-17 Female (Yellow)	
	FW Upgrade	1 x RJ-11 Female (Black)	
	Power	1 x 3-prong AC Socket (IEC60320/C14)	
Switches	Reset	1 x Semi-recessed Pushbutton	
	Power	1x Rocker	
	FW Upgrade	1 x Slide	
	LCD Control	4 x Pushbutton	
	LCD On/Off	1 x Pushbutton	
	Port	8 x Pushbutton	
LEDs	Online	8 (Orange)	
	Selected	8 (Green)	
	Power	KVM	1 (Dark Green)
		LCD	1 (Orange)
	Lock	Num	1 (Green)
		Caps	1 (Green)
		Scroll	1 (Green)
Emulation	Keyboard / Mouse	PS/2, USB	
Video	19-Inch LCD	1280×1024 @ 75 Hz ; DDC2B	
Scan Interval	1-255 seconds		
I/P Rating	100-240 VAC; 50/60 Hz; 1A		
Power Consumption	19-Inch LCD	120V, 22W	
Environment	Operating Temp.	0-50°C	
	Storage Temp.	-20-60°C	
	Humidity	0 - 80% RH, Non-condensing	
Physical Properties	Housing	Metal + Plastic	
	Weight	12.59 kg	
	Dimensions ( L x W x H )	48.30 x 68.92 x 4.40 cm	