

## Aten CL1316N 16-Port 19" LCD Integrated USB/PS2 Combo KVM Switcher

Computer Connections	Direct		16
	Maximum		256 (via Cascade)
Port Selection			OSD, Hotkeys, Pushbuttons
Connectors	KVM Ports		16 x SPHD-17 Female (Yellow)
	FW Upgrade		1 x RJ-11 Female (Black)
	Power		1 x 3-prong AC Socket (IEC60320/C14)
Switches	Reset		1 x Semi-recessed Pushbutton
	Power		1x Rocker
	FW Upgrade		1 x Slide
	LCD Control		4 x Pushbutton
	LCD On/Off		1 x Pushbutton
	Port		16 x Pushbutton
LEDs	Online		16 (Orange)
	Selected		16 (Green)
	Power	KVM	1 (Dark Green)
		LCD	1 (Orange)
	Lock	Num	1 (Green)
		Caps	1 (Green)
		Scroll	1 (Green)
Emulation	Keyboard / Mouse		PS/2, USB
Video	19-Inch LCD		1280×1024 @ 75 Hz; DDC2B
Scan Interval			1-255 seconds
I/P Rating			100-240 VAC; 50/60 Hz; 1A
Power Consumption	19-Inch LCD		120V, 22 W / 230V, 22.9 W
Environment	Operating Temp.		0-50°C
	Storage Temp.		-20-60°C
	Humidity		0 - 80% RH, Non-condensing
Physical Properties	Housing		Metal + Plastic
	Weight		12.58 kg
	Dimensions ( L x W x H )		68.90 x 48.30 x 4.40 cm