

## Aten CL5708N 8-Port 19in Single Rail LCD KVM Console

OS Compatibility	Windows: 2000 and up Linux: Redhat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 9.0 and up UNIX: AIX 4.3 and up; FreeBSD 4.2 and up; Sun Solaris 8 and up Novell: Netware 5.0 and up Mac: OS 9 and up DOS: 6.22
Max Computer Connections	Direct: 8
Daisy Chain (Cascade)	256 (via daisy-chain)
Console Connectors	Keyboard, mouse, and monitor: 1 x SPHD-18 male Flash ROM upgrade: 1 x RJ-11 female Computer/KVM: 8 x SPHD-15 female USB: 1 x USB Type-A female Daisy chain: 1 x DB-25 male
Switches	Power: 1 x rocker LCD power: 1 x pushbutton LCD Adjustment: 4 x pushbuttons Port selection: 2 x pushbuttons (port), 2 x pushbuttons (station) Firmware upgrade: 1 x slide Reset: 1 x semi-recessed pushbutton
LEDs	Port ID: 2 x 7-segment LED (yellow) Power on: 1 (dark green) LCD power: 1 (orange) Station ID: 2 x 7-segment LED (yellow) On Line: 8 (orange)
Emulation	Keyboard, mouse: PS/2, USB
Video Resolution	1280 x 1024 @ 75 Hz; DDC2B
Scan Interval	1 - 255 sec
Port Selection	OSD, Hotkey, Pushbutton
Enclosure	Metal and plastic
Power Requirements	110 - 230 VAC, 50 - 60 Hz, 1A
Power Consumption	27.5W, 95 BTU/h / 23W, 78 BTU/h
Environment	Operation temperature: 32 - 122°F (0 - 50°C) Storage temperature: -4 - 140°F (-20 - 60°C) Humidity 0 - 80% RH, Noncondensing
Dimensions (WxDxH)	18.9 x 24.9 x 1.7" (48.0 x 63.2 x 4.3 cm)
Weight	30.3 lbs (13.7 kg)