

Aten CL5716M 17in 16-Port Single Rail LCD KVM Console

Max Computer Connections	Direct: 16
Daisy Chain (Cascade)	512 (via Cascade)
Port Selection	OSD, Hotkey, Pushbutton
Console Connectors	Keyboard, mouse, and monitor: 1 x SPHD-18 male Flash ROM upgrade: 1 x RJ-11 female Mouse: 1 x USB Type-A female (white) Daisy chain: 1 x DB-25 male
Connectors	Power: 3 x prong AC socket Computer/KVM: 16 x SPHD-15 female (yellow) USB: 1 x USB Type-A female (white)
Switches	Power: 1 x rocker LCD power: 1 x pushbutton LCD Adjustment: 4 x pushbuttons Port selection: 2 x pushbuttons (port), 2 x pushbuttons (station) Firmware upgrade: 1 x slide Reset: 1 x semi-recessed pushbutton
LEDs	Port ID: 2 x 7-segment LED (yellow) Power on: 1 x (dark green) LCD power: 1 x (orange) Station ID: 2 x 7-segment LED (yellow) On Line: 16 (orange)
Video Resolution	1280 x 1024 at 75 Hz, DDC2B
Emulation	Keyboard, mouse: PS/2, USB
Scan Interval	1 to 255 sec
Keyboard	Language support: English (US), English (UK), German, German (Swiss), French, Spanish, Traditional Chinese, Japanese, Korean, Swedish, Italian, Russian, Hungarian, Greek
Power Requirements	110 to 240 VAC, 1 A
Power Consumption	27.5 W, 95 BTU/h/23 W, 78 BTU/h
Compliant	RoHS
Environment	Operation temperature: 32 to 122°F (0 to 50°C) Storage temperature: -4 to 140°F (-20 - 60°C) Humidity 0 to 80% RH, (Non-condensing)
Dimensions (W x D x H)	18.9 x 1.7 x 24.9" (48.0 x 4.3 x 63.2 cm)
Weight	31.3 lb (14.1 kg)