

Aten CL5716NUKit 16-port Slideaway LCD KVM Switch with Kit

Computer Connections	Direct: 16 Daisy Chain Maximum: 512
Port Selection	OSD, hotkey, pushbutton
Connectors	External Console Port: 1 x SPHD-18 Male External Mouse Port: 1 x USB Type A Female KVM Ports: 16 x SPHD-15/17 Female Daisy-chain Port: 1 x DB-25 Male FW Upgrade: 1 x RJ-11 Female Power: 1 x 3-prong AC socket USB Port: 1 x USB Type A Female
Switches	Reset: 1 x semi-recessed pushbutton Power: 1 x rocker switch Firmware Upgrade: 1 x switch LCD Adjust: 4 x pushbutton LCD On/Off: 1 x LED pushbutton Port Selection: 2 x pushbutton Station Selection: 2 x pushbutton
LED Indicators	16 x On Line 2 x Port ID 7-segment LED display 2 x Station ID 7-segment LED display 1 x Power 1 x Num Lock 1 x Caps Lock 1 x Scroll Lock
Emulation	Keyboard, Mouse: PS/2, USB
Video	1280 x 1024 @ 75 Hz, DDC2B
Scan Interval	1 to 255 sec
I/P Rating	100 to 240 VAC, 50 to 60 Hz, 1 A
Power Consumption	120 V, 26 W / 230 V, 26.8 W
Operating Temperature	32 to 104°F / 0 to 40°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Humidity	0 to 80% RH, non-condensing
Housing	Metal, plastic
Dimensions	27.1 x 19.1 x 1.7" / 68.9 x 48.5 x 4.4 cm 4 x 4.0' / 1.2 m USB cables 2 x 6.0' / 1.8 m USB cables 2 x 10.0' / 3.0 m USB cables
Weight	32.3 lb / 14.7 kg