

## Aten CL5800N 19in Dual Rail LCD Console

Connections	Direct computer connections: 1 Keyboard, mouse, and monitor: 1 x SPHD-18 Female Flash ROM upgrade: 1 x RJ-11 female Second console keyboard: 1 x 6-pin mini-DIN female Second console mouse: 1 x 6-pin mini-DIN female Second console video 1 x HDB-15 female USB: 1 x USB Type A female
Buttons or Switches	Reset: 1 x semi-recessed pushbutton Power: 1 x rocker Firmware upgrade: 1 x slide LCD power: 1 LCD adjustment: 4 x pushbutton
Video Resolution	1280 x 1024 @ 75 Hz; DDC2B
OS Compatibility	Windows: NT and up Linux: RedHat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 9.0 and up UNIX: AIX 4.3 and up; FreeBSD 4.2 and up; Sun Solaris 8 and up Novell: Netware 5.0 and up DOS: 6.2 and up
LEDs	Power on: 1 LCD power: 1
Emulation	Keyboard, mouse: PS/2, USB
Environment	Humidity: 0 - 80% RH, non-condensing Operational temperature: 32 - 104°F (0 - 40°C) Storage temperature: -4 - 140°F (-20 - 60°C)
Power Input Rating	100 - 240 VAC, 50/60 Hz
Power Consumption	27.4 W / 94 BTU/h; 28.0 W / 96 BTU/h
Dimension L x W x H	26.8 x 18.9 x 1.7" (68.0 x 48.0 x 4.4 cm)
Weight	32.5 lb (14.8 kg)