

## Aten CL5808N 8-Port 19in Dual Rail LCD Combo KVM Switch

Max Computer Connections	Direct: 8 Daisy chain or cascading: 256
Console Connectors	Keyboard, mouse, and monitor: 8 x SPHD-15/17 female Flash ROM upgrade: 1 x RJ-11 Secondary console: 1 x SPHD-18 male (additional console port) Extra mouse: 1 x USB Type A female USB peripheral: 1 x 1 x USB Type A female Daisy chain: 1 x DB-25 male
Video Resolution	Local: 19" LCD 1280 x 1024 @ 75 Hz; DDC2B Remote (from secondary console): 1920 x 1440
Scan Interval	1 - 255 sec.
Emulation	Keyboard and mouse: USB, PS/2
Port Selection	OSD, hotkeys, pushbuttons
Buttons or Switches	Port selection: 8 x pushbutton LCD adjustment: 4 x pushbutton LCD power: 1 x pushbutton Firmware upgrade: 1 x slide Power: 1 x rocker switch Reset: 1 x semi-recessed pushbutton
LED Indicators	On line: 8 x orange Selected: 8 x green Station ID: 2 x 7-segment LED display (orange) Power on: 1 x dark green
Enclosure	Metal / plastic
OS Compatibility	Windows: 2000 and up Linux: RedHat 7.1 and up; SuSE 9.0 and up; Mandriva (Mandrake) 9.0 and up UNIX: AIX 4.3 and up; FreeBSD 4.2 and up; Sun Solaris 8 and up Novell: Netware 5.0 and up Mac: OS 9 and up DOS: 6.22
Environment	Humidity: 0 - 80% RH, non-condensing Operation temperature: 32 - 122°F (0 - 50°C) Storage temperature: -4 - 140°F (-20 - 60°C)
Power Requirements	100 - 240 VAC, 50/60 Hz
Power Consumption	120 V, 30.1 W, 103 BTU ; 230 V, 30.7 W, 105 BTU
Dimensions (W x D x H)	26.8 x 18.9 x 1.7" (68.1 x 48.0 x 4.4 cm)
Weight	33.1 lbs (15.0 kg)