Aten CL5816N 16-Port Dual Rail LCD KVM Switch

Connections	Direct: 16 Daisy Chain/Cascading: 512 (Daisy Chain)
Port Selection	Hotkey, pushbuttons, OSD
Connectors	Console: Secondary Console: 1 x SPHD-18 Male (additional console port) Flash ROM Upgrade: 1 x RJ-11 Female Extra Mouse: 1 x RJ-11 Female USB Peripheral: 1 x USB Type-A Female (USB peripheral share) CPU: Keyboard/Mouse/Monitor: 16 x SPHD-15/17 Female Daisy Chain: 1 x DB-25 Male Power: 1 x 3-prong AC socket
Switches	Port Selection: 16 x Pushbutton LCD Adjustment: 4 x Pushbutton LCD Power: 1 x Pushbutton F/W Upgrade: 1 x Slide Power: 1 x Rocker Switch Reset: 1 x Semi-recessed Pushbutton
LED Indicators	Power On: 1 (dark green) On Line: 16 (orange) Station ID: 2 x 7 segment LED Display (orange) Selected: 16 (green)
Emulation	Keyboard/Mouse: PS/2/USB
Video Resolution	Local: 1280 x 1024 at 75 Hz, DDC2B (19" LCD) Remote: 1920 x 1440 (from secondary console)
Power Rating	Input: 100 to 240 V, 50 to 60 Hz (per AC power inlet)
Power Consumption	120 to 230 V, 26 to 26.8 W
Housing	Metal/Plastic
Dimensions (L x W x H)	18.9 x 26.8 x 1.7" (47.9 x 68.0 x 4.4 cm)
Weight	34.0 lb (15.4 kg)