

## Aten CL6708MW Single Rail 8-Port DVI FHD LCD KVM Switch

<b>Computer Connections</b>	
Direct	8
Maximum	64
Port Selection	OSD, Hotkey, Pushbutton
<b>Connectors</b>	
External Console Ports	1 x DVI-I Female, 2 x USB Type A Female, 1 x Mini Stereo Jack Female
External Mouse Port	1 x USB Type-A Female
KVM Ports	8 x DVI-I Female, 8 x USB Type A Female, 8 x Mini Stereo Jack Female
Firmware Upgrade	1 x RJ-11 Female
Power	1 x IEC60320/C14
<b>Switches</b>	
Reset	1 x Semi-recessed Pushbutton
Power	1 x Rocker Switch
Firmware Upgrade	1 x Slide Switch
LCD Adjustment	4 x Pushbutton
LCD On/Off	1 x Pushbutton
Port Selection	8 x Pushbutton
<b>LEDs</b>	
Online	8 (Orange)
Selected	8 (Green)
Power	1 x KVM Power(Dark Green) 1 x LCD Power(Orange)
Lock	1 x Num Lock (Green) 1 x Caps Lock (Green) 1 x Scroll Lock (Green)
<b>Panel Spec</b>	
LCD Module	17.3" TFT-LCD
Pixel Pitch	0.1989 mm x 0.1989 mm
Support Color	262144 colors
Contrast Ratio	650:1
Luminance	300 cd/m <sup>2</sup>
Response time	8 ms
Viewing Angle	140° (H), 120° (V)
<b>Emulation</b>	
Keyboard / Mouse	USB
Video	1920 x 1080 @ 60 Hz; DDC2B
Scan Interval	1-255 sec.
Maximum Input Power Rating	100-240 V AC, 50/60 Hz, 1 A
Power Consumption	110V, 29.26W ; 220V, 28.82W
<b>Environmental</b>	
Operating Temperature	0-40°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
<b>Physical Properties</b>	
Housing	Metal + Plastic
Weight	12.70 kg ( 27.97 lb )
Dimensions (L x W x H)	48.00 x 68.92 x 4.40 cm (18.9 x 27.13 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.