

Aten CS1642A 2-Port USB DVI Dual Display KVM Switch

Computer Connections	2
Port Selection	Hotkey, Pushbutton, Mouse
Connectors	
Console Ports	2 x USB Type A Female (White, rear panel) 2 x DVI-I Female (White) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)
KVM Ports	2 x USB Type B Female (white) 4 x DVI-I Female (white) 2 x Mini Stereo Jack Female (Green) 2 x Mini Stereo Jack Female (Pink)
Daisy Chain Ports	1 x RJ-45 Female (rear panel)
Power	1 x DC Jack
USB Hub	2 x USB Type A Female (Black; 1 x front panel; 1 x rear panel)
Switches	
Selected	3 x Pushbutton
Emulation	
Keyboard / Mouse	USB
Video	DVI Dual Link: 2560 x 1600 at 60Hz; 1920 x 1200 at 120Hz (3D Display)
Scan Interval	1-99 secs. (5 secs. default)
Power Consumption	DC 5.3 V, 10.6 W
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Plastic + Metal
Weight	0.56 kg (1.23 lb)
Dimensions (L x W x H)	26.23 x 7.68 x 4.40 cm (10.33 x 3.02 x 1.73 in.)