

## Aten CS1716A 16-Port PS/2-USB VGA KVM Switch with Daisy-Chain Port and USB Peripheral Support

Computer Connections	
Direct	16
Maximum	512 (via Daisy-chain)
Port Selection	OSD, Hotkey, Pushbutton
Connectors	
Console Ports	1 x SPHD-18 Male (Yellow)
KVM Ports	16 x SPHD-15/17 Female (Yellow)
Daisy Chain Ports	1 x DB-25 Female (Black) 1 x DB-25 Male (Black)
Firmware Upgrade	1 x RJ-11 Female (Black)
USB Port	1 x USB Type A Female
Power	1 x DC Jack Female (Black)
LEDs	
Online	16 (Orange)
Selected	16 (Green)
Station ID	1 x 2-digit, 7-segment (Orange)
Power	1 (Dark Green)
Switches	
Port Selection	16 x Pushbutton
Firmware Upgrade Recovery	1 x Slide
Emulation	
Keyboard / Mouse	PS/2, USB
Video	2048 x 1536; DDC2B
Scan Interval	1 - 255 Seconds (Default: 5 secs)
Power Consumption	DC 5.3 V; 6.6 W
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	2.85 kg ( 6.28 lb )
Dimensions (L x W x H)	43.72 x 15.99 x 4.40 cm (17.21 x 6.3 x 1.73 in.)