

Aten KH1516Ai 1-Local/Remote Share Access 16-Port Cat 5 KVM over IP Switch

Computer Connections	
Direct	16
Maximum	256 (via Daisy-chain)
Port Selection	OSD, Hotkey, Pushbutton
Connectors	
Console Ports	2 x USB Type A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDB-15 Female (Blue)
KVM Ports	16 x RJ-45 Female
Daisy Chain Ports	1 x DB-25 Male (Black)
Power	1 x IEC 60320/C14
LAN Ports	1 x RJ-45 Female
Firmware Upgrade	1 x RJ-11 Female (Black)
PON	1 X RJ-45 Female
Laptop USB Console (LUC) Port	1 x USB Mini Type B Female (Black)
Switches	
Reset	1 x Semi-recessed Pushbutton
Power	1 x Rocker
Port Selection	16 x Pushbutton
LEDs	
Online	16 (Green)
Selected	16 (Orange)
Power	1 (Blue)
Station ID	1 x 2-digit 7-segment (Orange)
Link	1 (Orange)
10/100 Mbps	1 (Orange / Green)
Emulation	
Keyboard / Mouse	PS/2; USB
Video	
Local	1600 x 1200 @ 60 Hz (40m) ; 1280 x 1024 @ 75 Hz (50 m with KA7xx Adapter Cable)
Remote	1600 x 1200 @ 60Hz
Scan Interval	1-255 secs
Maximum Input Power Rating	100-240 VAC; 50/60 Hz; 1A
Power Consumption	120V/12.5W; 230V/12.7W
Environmental	
Operating Temperature	0 - 40°C
Storage Temperature	-20 - 60°C
Humidity	0-80% RH; Non-condensing
Physical Properties	
Housing	Metal
Weight	2.83 kg (6.23 lb)
Dimensions (L x W x H)	43.72 x 15.58 x 4.40 cm (17.21 x 6.13 x 1.73 in.)