

Aten KH2516A 2-Console 16-Port Cat 5 KVM Switch with Daisy-Chain Port

| | |
|----------------------------|---|
| Computer Connections | |
| Direct | 16 |
| Maximum | 256 (via Daisy-chain) |
| Port Selection | OSD, Hotkey, Pushbutton |
| Connectors | |
| Console Ports | 4 x USB Type A Female (White) 2 x 6-pin Mini-DIN Female (Purple) 2 x 6-pin Mini-DIN Female (Green) 2 x HDB-15 Female (Blue) |
| KVM Ports | 16 x RJ-45 Female |
| Daisy Chain Ports | 1 x DB-25 Female (Black) 1 x DB-25 Male (Black) |
| Firmware Upgrade | 1 x RJ-11 Female |
| Power | 1 x IEC 60320/C14 |
| Switches | |
| Port Selection | 16 x Pushbutton |
| Console Selection | 2 x Pushbutton |
| Reset | 1 x Semi-recessed Pushbutton |
| Firmware Upgrade | 1 x Slide |
| Power | 1 x Rocker |
| LEDs | |
| Online | 16 (Green) |
| Selected | 16 (Orange) |
| Console | 2 (Orange) |
| Power | 1 (Blue) |
| Station ID | 1 x 7-segment LED display (Orange) |
| Emulation | |
| Keyboard / Mouse | PS/2; USB |
| Scan Interval | 1-255 Seconds |
| Video | 1600 x 1200 @ 60 Hz (40m); 1280 x 1024 @ 75 Hz (50m) |
| Maximum Input Power Rating | 100-240 VAC; 50/60 Hz; 1A |
| Power Consumption | 120V/7.6W; 230V/9.0W |
| Environmental | |
| Operating Temperature | 0-50°C |
| Storage Temperature | -20-60°C |
| Humidity | 0-80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 2.85 kg (6.28 lb) |
| Dimensions (L x W x H) | 43.72 x 15.58 x 4.40 cm (17.21 x 6.13 x 1.73 in.) |