

## Aten KL1508AM 8-Port Cat 5 Dual Rail 17in LCD KVM Switch

OS Compatibility	Windows: 2000 and up Linux: RedHat 6.0 and up; SuSE 8.2 and up; Mandriva (Mandrake) 9.0 and up UNIX: AIX 4.3 and up; FreeBSD 3.51 and up; Sun Solaris 8 and up Novell: Netware 5.0 and up Mac: OS 9 and up DOS: 6.2 and up
Max Computer Connections	Direct: 8 Via daisy chain: 256
Connectors	Secondary console connections: 1 x USB Type A female, 1 x 6-pin mini-DIN female Keyboard, mouse, and monitor: 8 x RJ-45 Flash ROM upgrade: 1 x RJ11 Daisy chain: 1 x DB-25 male
Buttons or Switches	Reset: 1 x semi recessed pushbutton Power: 1 x rocker Firmware upgrade: 1 x slide LCD adjust: 4 x pushbutton LCD power: 1 x pushbutton Station selection: 2 x pushbutton Port selection: 8 x pushbutton
Emulation	Keyboard, mouse: PS/2, USB, serial
LED Indicators	Power on: 1 x (blue) On line: 8 x (green) Station ID: 2 x 7-segment (red) Selected: 8 x (red)
Video Resolution	1280 x 1024 @ 75 Hz; DDC2B
Scan Interval	1 - 255 sec
Port Selection	OSD, hotkey, pushbutton
Enclosure	Metal
Environment	Operating temperature: 32 - 104°F (0 - 40°C) Storage temperature: -4 - 140°F (-20 - 60°C) Humidity: 0-80% RH, non-condensing
Power Consumption	120 V / 24 W; 230 V / 24 W
Power Requirements	100 - 240 VAC; 50/60 Hz; 1A
Dimensions (L x W x H)	28.0 x 19.0 x 1.7" (70.9 x 48.2 x 4.4 cm)
Weight	38.1 lb (17.3 kg)