

## Aten KL1516AiN 16-Port 19in Dual Rail CAT5 LCD KVM Over the Net

Computer Connections	Direct: 16 Maximum: 256 (via Daisy-Chain)
Console Connections	Local/Remote: 1
Port Selection	OSD, Hotkey, Pushbutton
Connectors	Console Ports Keyboard: 1 x 6-pin mini-DIN female (purple) 1 x USB Type A female (white) Video: 1 x HDB-15 female (blue) Mouse: 1 x 6-pin Mini-DIN female (green) 1 x USB Type A female (white) KVM Ports: 16 x RJ-45 female Daisy Chain: 1 x DB-25 Male (black) Power: 1 x 3-prong AC socket F/W Upgrade: 1 x RJ-11 Female (black) External Mouse: 1 x USB Type A (female) LAN: 1 x RJ-45 female PON: 1 x RJ-45 female
Switches	Power: 1 x Rocker LCD power: 1 x Pushbutton LCM Adjustment: 4 x Pushbuttons Port selection: 16 x Pushbuttons Firmware upgrade: 1 x Slide KVM Reset: 1 x Semi-recessed pushbutton Station: 2 x Pushbuttons
LEDs	Station ID: 2 x 7-segment (orange) Port on Line: 16 (green) Port Selected: 16 (orange) Power: 1 (blue) Num/Caps/Scroll Lock: 1 (green) Link: 1 (Green) 10/100 Mb/s: 1 (orange/green) LCD Power: 1 (orange)
Video Resolution	Local: 1280 x 1024 at 75 Hz, DDC2B (165'/50 m) Remote: 1600 x 1200 at 60 Hz, DDC2B (130'/40 m)
Emulation	Keyboard/mouse: PS/2, USB
Scan Interval	1 to 255 sec
Housing	Metal
Language Supported	English (US); English (UK), German, German (Swiss), French, Spanish, Traditional Chinese; Japanese, Korean, Swedish, Italian, Russian, Hungarian, Greek
Power	Input: 100 to 240 VAC, 50/60 Hz, 1 A Consumption: 120 V, 27.5 W 230 V, 27.5 W
Temperature	Operating: 32 to 104°F (0 to 40°C) Storage: -4 to 140°F (-20 to 60°C) Humidity: 0 to 80% RH (non-condensing)
Compliance	RoHS
Dimensions	18.89 x 27.6 x 1.73" (48 x 70.1 x 4.4 cm)
Weight	33.95 lb (15.4 kg)