

## Aten KL1516AM 16-Port CAT5 Dual Rail LCD KVM Switch

Connections	Direct: 16 Daisy Chain/Cascading: 512 (Daisy Chain)
Port Selection	Hotkey, pushbuttons, OSD
Connectors	Secondary Console: 1 x USB Type A Female 1 x 6-pin Mini-DIN Female 1 x VGA Female CPU: Keyboard/Mouse/Monitor: 16 x RJ-45 ports Flash ROM Upgrade: 1 x RJ-11 Daisy Chain: 1 x DB-25 Male
Indicators and Controls	LED Indicators: Power On: 1 On Line: 16 Station ID: 2 x 7 segment Selected: 16
Emulation	Keyboard/Mouse: PS/2/USB/Serial
Video Resolution	1280 x 1024 at 75Hz, DDC2B
Scan Interval	1 to 255 sec
Power Consumption	100 to 230 V, 24.5 W
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-4 to +140°F (-20 to +60°C)
Relative Humidity	0 to 80% RH (non-condensing)
Housing	Metal
Dimensions (L x W x H)	28.0 x 19.0 x 1.7" / 71.1 x 48.3 x 4.3 cm
Weight	38.1 lb / 17.3 kg