

Aten KL1516AN 16-Port CAT5 Dual Rail LCD KVM Switch

Connections	Direct: 16 Daisy Chain/Cascading: 512 (Daisy Chain)
Port Selection	Hotkey, pushbuttons, OSD
Connectors	Secondary Console: 3 x 6-pin Mini-DIN Female 2 x USB Type A Female 1 x VGA Female 1 x RJ-11 CPU: 16 x RJ-45 Power: 1 x 3-prong AC socket
Indicators and Controls	LED Indicators: Power On: 1 Selected: 16 Station ID: 2 x 7 segment Port ID: 2 x 7 segment LCD Power: 1 Switches: Power: 1 x Rocker Reset: 1 x Semi-recessed pushbutton Port Selection: 2 x Pushbutton (station), 2 x Pushbutton (port) LCD Adjustment: 4 x Pushbutton F/W Upgrade: 1 x Slide
Emulation	Keyboard/Mouse: PS/2
Video Resolution	1280 x 1024 at 75Hz, DDC2B
Scan Interval	1 to 255 sec
Power Consumption	100 V, 23 W / 230 V, 23 W
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-4 to +140°F (-20 to +60°C)
Relative Humidity	0 to 80% RH (non-condensing)
Housing	Metal
Dimensions (L x W x H)	18.9 x 27.6 x 1.7" / 48.0 x 70.1 x 4.4 cm
Weight	38.1 lb / 17.3 kg