

Aten KL1516ANUKit 16-Port CAT5 Dual Rail LCD KVM Switcher

| | |
|-------------------------|--|
| Connections | Direct: 16 Daisy Chain/Cascading: 512 (Daisy Chain) |
| Port Selection | Hotkey, pushbuttons, OSD |
| Connectors | Secondary Console: 3 x 6-pin Mini-DIN Female 2 x USB Type A Female 1 x VGA Female 1 x RJ-11 CPU: 16 x RJ-45 Power: 1 x 3-prong AC socket |
| Indicators and Controls | LED Indicators: Power On: 1 Selected: 16 Station ID: 2 x 7 segment Port ID: 2 x 7 segment LCD Power: 1 Switches: Power: 1 x Rocker Reset: 1 x Semi-recessed pushbutton Port Selection: 2 x Pushbutton (station), 2 x Pushbutton (port) LCD Adjustment: 4 x Pushbutton F/W Upgrade: 1 x Slide |
| Emulation | Keyboard/Mouse: PS/2 |
| Video Resolution | 1280 x 1024 at 75Hz, DDC2B |
| Scan Interval | 1 to 255 sec |
| Power Consumption | 100 V, 23 W / 230 V, 23 W |
| Operating Temperature | 32 to 104°F (0 to 40°C) |
| Storage Temperature | -4 to +140°F (-20 to +60°C) |
| Relative Humidity | 0 to 80% RH (non-condensing) |
| Housing | Metal |
| Dimensions (L x W x H) | 18.9 x 27.6 x 1.7" / 48.0 x 70.1 x 4.4 cm |
| Weight | 38.1 lb / 17.3 kg |