

Aten KN2116VA 16-Port Cat 5 KVM over IP Switch with Virtual Media

Computer Connections	
Maximum	256 (via Cascade KVM Switches)
Direct	16
Console Connections	
Remote	2
Local	1
Port Selection	Pushbuttons, Hotkeys, GUI
Connectors	
Console Ports	2 x USB Female (White) 1 x DVI-D Female (White) 1 x VGA HDB-15 (Blue) 1 x RJ-45 Female (Black)
KVM Ports	16 x RJ-45 Female (Black)
USB Port	3 x USB Female (White)
Audio	2 x Audio Jack Female (Pink; Green)
Laptop USB Console (LUC) Port	1 x Mini-USB Female (Black)
PON	1 x RJ-45 Female (Black)
Serial	1 x RJ-45 Female (Black)
LAN Ports	2 x RJ-45 Female (Black)
Power	2 x IEC 60320/C14
Switches	
Power	2 x Rocker Switches
Port Selection	2 x Pushbuttons
Reset	1 x Semi-recessed Pushbutton
LEDs	
Online / Selected	16 (Green/Orange)
Power	2 (Blue)
Link 10 / 100 / 1000 Mbps	2 (Red/Orange/Green)
Emulation	
Keyboard / Mouse	PS/2; USB
Video	
Local	1920 x 1200 @ 60Hz
Remote	1920 x 1200 @ 60Hz
Maximum Input Power Rating	100-240V~ ; 50-60Hz; 1A
Power Consumption	
Single Power	110V/34.54W; 220V/34.76W
Dual Power	110V/17.67W; 220V/17.93W (per input)
Scan Interval	1 - 255 Sec
Environmental	
Operating Temperature	0 - 40°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	5.56 kg (12.25 lb)
Dimensions (L x W x H)	43.36 x 41.21 x 4.40 cm (17.07 x 16.22 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

