

Aten VM0404 4x4 VGA/Audio Matrix Switch

Video Input	
Interfaces	4 x HDB-15 Male (Blue)
Impedance	75 ohm
Max. Distance	1.8 m
Video Output	
Interfaces	4 x HDB-15 Female (Blue)
Impedance	75 Ω
Max. Distance	30 m
Video	
Max. Bandwidth	300 MHz
Max. Resolution	Up to 1920 x 1200
Max. Distance	Up to 30 m
Audio	
Input	4 x Mini Stereo Jack Female (Green)
Output	4 x Mini Stereo Jack Female (Green)
Control	
RS-232	Connector: 1 x DB-9 Female (Black) Baud rate and protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No
IR	1 x Mini Stereo Jack Female (Black)
EDID Settings	EDID Mode: Default / Port1 / Remix / Auto
Power	
Connectors	1 x DC Jack (Black)
Consumption	5.3 VDC, 2.7W
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.87 kg (1.92 lb)
Dimensions (L x W x H)	26.00 x 7.61 x 4.40 cm (10.24 x 3 x 1.73 in.)
Carton Lot	5 pcs