

## Aten VM7514 4-Port HDBaseT Input Board

<b>Video Input</b>	
Interfaces	4 x RJ-45 Female (Silver)
Impedance	100 $\Omega$
<b>Video</b>	
Max. Data Rate	10.2 Gbps (3.4 Gbps per lane)
Max. Pixel Clock	340 MHz
Compliance	HDBaseT, HDCP 1.4 compatible Consumer Electronics Control (CEC)
Max. Resolution	Up to 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)
Max. Distance	100 m (Cat 6a)
<b>Control</b>	
RS-232	4 x Captive Screw Connectors, 3 pole
IR	4 x Mini Stereo Jack Female (Black)
<b>Power</b>	
Consumption	24.5 W
<b>Environmental</b>	
Operating Temperature	0-40°C
Storage Temperature	-20-60°C
Humidity	0 - 80% RH, Non-Condensing
<b>Physical Properties</b>	
Housing	Metal
Weight	0.64 kg ( 1.41 lb )
Dimensions (L x W x H)	35.20 x 23.70 x 2.28 cm (13.86 x 9.33 x 0.9 in.)