

Aten VS1504T Four-Port Cat5 Audio/Video Splitter

| | |
|----------------------------|--|
| Video Connector | Input: 1 x 15-Pin VGA, male Output: 1 x 15-Pin VGA, female |
| Outputs | Input: 1 x 3.5 mm Mini stereo jack, female Output: 1 x 3.5 mm Mini stereo jack, female |
| Connectors | Unit to Unit: 4 x RJ-45, female Cascade In: 1 x RJ-45, female |
| RS-232 | 1 x DB-9, female 1 x DB-9, male |
| Power | 1 x DC jack |
| Switches | 2 x Pushbuttons (local RS-232 port, group screen on/off) |
| LEDs | Power (orange) Local RS-232 port (green) Group screen on/off (green) |
| Video Resolution Supported | 1920 x 1200, 60 Hz at 98.4' / 30 m 1600 x 1200, 60 Hz at 492.1' / 150 m 1280 x 1024, 60 Hz at 656.2' / 200 m |
| Transmission Distance | 492.1' / 150 m |
| Power Consumption | 5.3 VDC, 4.7 W |
| Compatible Receivers | Suggested ATEN VB552, VE200, and VE200R |
| Temperature | Operating: 32 to 122°F / 0 to 50°C Storage: -4 to 140°F / -20 to 60°C |
| Humidity | 0 to 80% RH, Non-condensing |
| Dimensions (LxWxH) | 8.3 x 3.5 x 2.2" / 21.0 x 8.8 x 5.6 cm |
| Weight | 1.7 lb / 0.8 kg |