

AJA KUMO CP 1RU Control Panel for KUMO 1604/1616/3232 Routers

User Interface	<ul style="list-style-type: none">• 40 buttons with removable overcap for lens chips• Includes factory installed lens chip set• High and Low button tally indication, configurable brightness• Controls up to four KUMO routers• Panel Lock feature• Destination Lock feature
Router Support	<ul style="list-style-type: none">• KUMO 1604• KUMO 1616• KUMO 3232• KUMO 6464 (First 32 I/O in Normal Mode)• KUMO 1616-12G• KUMO 3232-12G
Network Interface	<ul style="list-style-type: none">• 1x RJ-45, 10/100/1000 Ethernet• Embedded web server for remote control
USB Interface	<ul style="list-style-type: none">• 1x Mini-USB for IP configuration using AJA eMini-Setup
Size (w x d x h)	<ul style="list-style-type: none">• 1RU - 17.4" x 1.3" x 1.75" (441.96 x 33.02 x 44.45 mm)
Weight	<ul style="list-style-type: none">• 1.2 lb (0.6 kg)
Power	<ul style="list-style-type: none">• 10-14 VDC regulated, 2.5W typical, 6W max, power supply required, included with purchase• AC Adapter: 100-240VAC, 50/60 Hz, universal input
Environment	<ul style="list-style-type: none">• Safe Operating Temperature: 0 to 40 C (32 to 104 F)• Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)• Operating Relative Humidity: 10-90% noncondensing• Operating Altitude: <3,000 meters (<10,000 feet)