

A-NeuVideo ANI-PIP-LITE 2x1 HDMI Multiviewer with PIP

- **Video Bandwidth:** 225MHz/6.75Gbps
- **Input Ports:** (2) HDMI (Female type)
- **Output Ports:** (1) HDMI (Female type)
- **Audio Output:** PCM2, 5.1, 7.1CH, Dolby 5.1, DTS5.1
- **Input Resolutions:** 480i60Hz, 480p60Hz, 576i50Hz, 576p50Hz, 720p50/60Hz, 1080i50/60Hz, 1080p24/30/50/60Hz, 800x600@60, 1024x768@60, 1280x720@60, 1920x1080@60
- **Output Resolutions:** 1080p, 720p, 1080i, 1024x768, 1360x768
- **ESD Protection:** Human Body Model: $\pm 8\text{kV}$ (air-gap discharge) / $\pm 4\text{kV}$ (contact discharge)
- **Dimensions (WxDxH):** 2.6 x 5.5 x 1 in (70x140x25mm)
- **Weight:** .7 lb (300g)
- **Chassis Material:** Metal
- **Operating Temperature:** 0°C~40°C/ 32°F~104°F
- **Storage Temperature:** -20°C ~ 60°C/-4°F ~140°F
- **Relative Humidity:** 20~90% RH (non-condensing)
- **Power Consumption (Max):** 10W
- **Power Supply:** 5V/1A DC (US/EU standards, CE/FCC/UL certified)