

Smartavi MXC-HD12X32S 12X32 HDMI/RS-232/IR Expandable Matrix Switcher

HDMI VIDEO INPUT	
Format	HDMI 1.3b [Deep Color, xvYcc color space supported]
DVI Compliance	Single-link DVI-D 1.1
HDCP Compliance	1.0/1.1
Video Bandwidth	Single-link 340MHz [10.2Gbps]
Resolution	480i,480p,720i,720p,1080i, 1080p
Input Interface	(1) HDMI [7.1ch audio & video]
Connector	Type A[19-pin female]
Maximum Distance	25 ft.
HDMI VIDEO OUTPUT	
Format	HDMI 1.3b [Deep Color, xvYcc color space supported]
DVI Compliance	Single-link DVI-D 1.1
HDCP Compliance	1.0/1.1
Video Bandwidth	Single-link 340MHz [10.2Gbps]
Resolution	480i,480p,720i,720p,1080i, 1080p
Input Interface	(1) HDMI [7.1ch audio & video]
Connector	Type A[19-pin female]
Maximum Distance	25 ft.
RCA AUDIO OUTPUT	
Frequency Response	20 Hz to 20 KHz
Impedance	600 ohm
Nominal Level	0-1.0 V
Common Mode	Rejection at 60dB
Output Interface	Right/Left RCA Female
S/PDIF AUDIO OUTPUT	
Frequency Response	20 Hz to 20 KHz
Impedance	600 ohm
Nominal Level	0-1.0 V
Common Mode	Rejection at 60dB
Output Interface	Right/Left RCA Female
OTHER	
Power	External 100-240 VAC/5VDC2A @10W
Dimensions	17.125 in W x 12 in H x 12 in D
Weight	20 lbs
Operating Temp.	0-55 °C (32-131°F)
Storage Temp.	-20-85 °C (-4-185 °F)
Humidity	Up to 95%