

INPUTS

2 HDMI: On female HDMI connectors

OUTPUTS

1 HDBaseT: On an RJ-45 connector

VIDEO

Max. Data Rate: 8.91Gbps (2.97Gbps per graphic channel)

Max. Resolution: 4K@60Hz (4:2:0)

Standards Compliance: HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 1.4

USER INTERFACE

Controls: Last connected/priority DIP-switches and toggles to select the input manually

ENCLOSURE

Size: 1 Gang wall plate

Cooling: Passive heat sink (metal sheet)

REGULATORY COMPLIANCE

EMC EN 55032

IEC 60950-1(ed.2)

IEC 60950-1(ed.2)am1

IEC 60950-1(ed.2)am2

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

POWER

Source: 5V DC

Consumption: 780mA

ACCESSORIES

Included with all versions: 1 Power adapter, 1 power cord

Included with US-D version: 2 US Frame sets and faceplates (1 in black and 1 in white)

Included with European version: 1 EU white frame, 1 UK white frame, 1 EU/UK white faceplate

PRODUCT DIMENSION

UK: 8.60cm x 3.80cm x 8.60cm (3.39" x 1.50" x 3.39") W, D, H

8.00cm x 3.80cm x 8.00cm (3.15" x 1.50" x 3.15") W, D, H

EU: 8.00cm x 3.80cm x 8.00cm (3.15" x 1.50" x 3.15") W, D, H

US: 6.98cm x 3.70cm x 11.43cm (2.75" x 1.46" x 4.50") W, D, H

PRODUCT WEIGHT

UK: 0.2kg (0.4lbs) approx.

0.2kg (0.4lbs) approx.

EU: 0.2kg (0.4lbs) approx.

US: 0.2kg (0.4lbs) approx.

SHIPPING DIMENSION

UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

EU: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

US: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

SHIPPING WEIGHT

UK: 0.6kg (1.2lbs) approx.

0.6kg (1.2lbs) approx.

EU: 0.6kg (1.2lbs) approx.

US: 0.6kg (1.2lbs) approx.
