

Kramer BC-2S18-100M 18 AWG 2-Conductor Speaker Cable - 100m

CONSTRUCTION	
CONDUCTORS:	2.
AWG:	18.
STRANDING:	7x26.
CONDUCTOR MATERIAL:	Bare copper.
INSULATION:	Polypropylene, wall thickness 0.008".
OUTER SHIELD MATERIAL:	Unshielded.
OUTER JACKET MATERIAL:	PVC - Polyvinyl chloride, wall thickness 0.017".
OUTER JACKET RIPCORD:	Yes.
ELECTRICAL	
NOM. INDUCTANCE:	0.145 (μ H/ft).
NOM. CAPACITANCE CONDUCTOR TO CONDUCTOR:	21.500 (pF/ft).
NOM. CONDUCTOR DC RESISTANCE:	6.5 Ω /1000ft @20°C.
MAX. OPERATING VOLTAGE (UL):	300V RMS.
MAX. RECOMMENDED CURRENT:	5A per conductor @25°C ambient.
OVERALL	
OVERALL CABLING LAY LENGTH & DIRECTION:	3.5" lay length, 3.4 twists/ft.
OPERATING TEMPERATURE RANGE:	-20° to +75°C (-4° to 167°F).
UL TEMPERATURE RATING:	75°C (167°F).
BULK CABLE WEIGHT:	53.6lbs/1000ft.
MAX. RECOMMENDED PULLING TENSION:	152lbs.
MIN. BEND RADIUS/MINOR AXIS:	2.625" (66.6mm).
OVERALL NOMINAL DIAMETER:	0.158" (4.0mm).