



Description: The Rockustics OneSub & DubSub subwoofers are built with a durable, rock enclosure designed to withstand rain, frost, snow, and ice.

The OneSub is a stand-alone, passive sub that requires a sub amplifier with an active crossover.

The DubSub functions as a Sub/Sat system. Simply wire two additional, full-range speakers to the DubSub and create a three speaker sub/sat system that can then be powered by any traditional amplifier with no need for a sub amp or external crossover.

Features:

- One active driver and one passive
- Color options: Gray, Sandstone, or Brown

Applications:

The OneSub & DubSub are ideal choices for any outdoor setting.

Rockustics®

13720 W. 109th St.
 Lenexa, KS 66215
 Phone: 913.663.5600
 Fax: 913.663.3200
www.rockustics.com

ONESUB & DUBSUB PRODUCT SPECIFICATIONS

IMPEDANCE (Nominal)	4 Ω
SENSITIVITY dB @ 1W/1M	87 dB
SENSITIVITY dB @ 2.83V/1M	90 dB
FREQUENCY RESPONSE (±3 dB)	38 Hz - 100Hz
FREQUENCY RESPONSE (±10 dB)	32 Hz - 100Hz
MAX. PROGRAM POWER	350 W
MAX. CONTINUOUS POWER RMS	200 W
MAX. POWER SPL @ 1M	107 dB
TAP SELECTOR	Wire Leads
TRANSDUCER - LOW FREQUENCY	8" Woofers
INPUTS	Wire Leads
COLORS	Brown, Gray, or Sandstone
HEIGHT (SM = HEIGHT)	292.1 mm / 11.5"
WIDTH (SM = WIDTH)	533.4 mm / 21"
WEIGHT	38.6 kg / 85 lb
SHIPPING WEIGHT	39.6 kg / 87 lb
REGULATORY - CE	Approved
ACCESSORIES OPTIONAL	120 W XFMR, Security Bracket (RSB1)
APPLICATIONS	Gardens, patios, pool areas, restaurants, theme parks, outdoor settings