

ViewZ VZ-FMS-2 2.1MP 3G/HD-SDI Full HD Miniature Box Camera

| | |
|--------------------------|--|
| Imaging Sensor | 2.1 Megapixel CMOS Sensor |
| Scanning System | 1/3" Progressive Scan |
| Image Frame | NTSC, PAL Composite (1.0Vp-p ,75ohm) |
| Electronic Shutter Speed | MANUAL(1/30(25) ~ 1/30,000 sec) |
| Horizontal TVL | More than 1000 TVL |
| S/N Ratio | More than 50dB (AGC Off) |
| HD-SDI Video Output Mode | HD-SDI, 3G-SDI |
| | 1080p / 29.97, 59.94fps |
| | 1080i / 59.94fps |
| | 720p / 29.97, 59.94fps |
| | Composite(1.0Vp-p ,75ohm), Color Bar Signal |
| Auto White Balance | AUTO/AUTOEXT/PRESET / Manual (R-Gain, B-Gain) |
| Min. Illumination | 0.1Lux (F1.2, 50 IRE, AGC MAX) / DSS X4:0.01 Lux |
| Digital Noise Reduction | DNR (Off / Low / Middle / High) |
| Backlight Compensation | BLC (Off / On) |
| Wide Dynamic-Range | WDR (Off / Low / Middle / High) |
| SENS-UP | OFF / x2 / x3 / x4 |
| AGC | Adjustable 0 ~ 10 |
| Color Temp / R & B-Gain | Adjustable |
| Language | English (Selectable) |
| Mirror Image | MIRROR, FLIP (Off / On) |
| Camera ID | Support |
| Digital Zoom | Support |
| Privacy Masking | Support |
| Motion Detection | Support |

Interface

| | |
|-----------|---|
| HD/3G-SDI | 1 |
| DC 12V | 1 |

Dimensions & Weight

| | |
|------------------------------------|--------------------------------|
| Outline Dimension (W x H x D) inch | 0.9" x 0.9" x 1.45" |
| (W x H x D) millimeter | 23.0 mm x 23.0 mm x 37.0 mm |
| Net Weight | 0.11 lbs / 50g (Without Cable) |

General Summary

| | |
|--------------------------|------------------------------------|
| Construc on | Aluminium Alloy |
| LENS Mount | Fix 1/2.5" 3.6mm,M12 (Option: 6mm) |
| Operating Temp | 14 - 122 °F / -10°C ~ 50°C |
| Operating Temp | 14 - 122 °F / -10°C ~ 50°C |
| Storage Temp | -4 ~ 158°F / -20°C ~ 70°C |
| Humidity | 0% to 90% Non-condensing |
| Supplied Voltage | DC12V 150mA |
| Power - Consumption | 1.8 W |
| Warranty - Parts / Labor | 2 Years |