

SWIT FM-24DCi 24-inch DCI-P3 Gamut Post Production Monitor

LCD Performance		
Size	24 inches	
Display area	518.4x324mm	
Resolution	1920x1080	
Aspect ratio	16:10	
Brightness	250cd/m2	
Contrast	1000:1	
Color	1.073G colors, 10 bit	
Viewing Angle	Horizontal: 178°; Vertical: 178°	
Input		
BNC x2	3G/HD/SD-SDI input	
HDMI x1	HDMI 1.3 input	
RJ45 x1	10M/100M Ethernet input	
Output		
BNC x2	3G/HD/SD-SDI loop output	
USB x2	5V / 1A power output	
2-pin LEMO x1	Battery power output	
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-260M	1035i (60 / 59.94)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
HDMI	480i/ 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
General		
Input voltage	DC 12V-17V 5A, AC 100-240V, 50/60Hz	
Power consumption	100W	
Working temperature	0°C■+50°C	
Working humidity	10%■90%	
Storage temperature	-15°C■+60°C	
Storage humidity	10%■90%	
Dimensions	569.9x380.7x90.5mm	
Net weight (main body)	9.05kg	