

Apantac HDBT-SET-2 HDMI Extender (Transmitter/Receiver) Kit with Ethernet and PoE

EXTENDER	
Input	1 x HDMI (A type female) 1 x RS232 4 x RJ45 (10/100 Base-T Ethernet) 1 x IR (3.5 mm jack)
Output	1 x RJ45 (link) 1 x HDMI (bypass) 1 x IR out (3.5 mm jack for emitter)
Maximum Resolution / Distance	Maximum resolution of 1920 x 1200 (including 1080p at 60 Hz and 3D) up to 330' (100 m)
Ethernet	10/100 Base-T (IEEE 802.3/3u/3x)
Power	48 VDC
Dimensions (W x D x H)	6.73 x 4.72 x 0.98" (171 x 120 x 25 mm)
RECEIVER	
Input	1 x RJ45 (link) 4 x RJ45 (10/100 Base-T Ethernet) 1 x direct IR receiver (on top) 1 x extended IR receiver (3.5 mm jack)
Output	1 x HDMI (A type female) 1 x RS232
Maximum Resolution / Distance	Maximum resolution of 1920 x 1200 (including 1080p at 60 Hz and 3D) up to 330' (100 m)
Ethernet	10/100 Base-T (IEEE 802.3/3u/3x)
Power	PoE
Dimensions (W x D x H)	6.73 x 4.72 x 0.98" (171 x 120 x 25 mm)