

Apantac KVM-SET-4 VGA/USB over CATx KVM-1-EU and KVM-1-RU Extender (Transmitter/Receiver) Kit

Connectors	Extender: 1 x USB keyboard input 1 x USB Mouse input 1 x 3.5 mm phone jack, audio input 1 x 15-pin Sub-D female, PC input 1 x RJ-45, system link 1 x 15-pin Sub-D VGA female, local monitor output 1 x 3.5 mm phone jack, audio output Receiver: 1 x RJ-45, system link 1 x 5 VDC input 1 x 15-pin Sub-D VGA female, local monitor output 1 x USB type A female, mouse 1 x USB type A female, keyboard
Indicators	Each Unit: 1 x USB Status
Controls	Receiver: 1 x Gain, rotary knob 1 x Focus, rotary knob
Power Connector	1 x 5 VDC barrel, power input
Control	Receiver: 1 x EQ control rotary knob
Adjustments	Receiver: equalizer
Maximum Resolution	2048 x 1536
Distance	Up to 1000' (300 m)
Mount	Magnetic
Power	Extender: 5 VDC, 1000 mA (from USB or optional DC) Receiver: 5 VDC, 1000 mA
Dimensions (W x D x H)	Each Unit: 2.4 x 4.4 x 1.1" (6.2 x 11.3 x 2.9 cm)
Weight	Both Units: 4.0 lb (1.8 kg)