


COMPACT UP/DOWN/CROSS CONVERTER

- Compact Up/Down/Cross Converter • Supports 3G/HD-SDI/CV input in 50/60Hz
- HDMI and SDI output with embedded audio for monitoring • Supports 8 embedded audio
- Stereo analog audio output • Front panel buttons to recall presets • IP control

Micro-UDX

Compact Up / Down / Cross Converter



Micro-UDX			
Video Inputs	3G/HD/SD-SDI	Outputs	1 x HDMI, 1 SDI
Total Windows	1	HDMI	480P, 720P, and 1080p 50/60 Hz
Serial Digital	SMPTE 424M, 292M, 259M	SDI	Matching HDMI output resolution up to 3G
Equalization	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	On Screen Display	N/A
Return Loss	> 15db up to 1.485 Gbps < > 10db up to 3G	GPI	N/A
Embedded Audio	SMPTE-272M-A	IP	100 BaseTx, TSL, AXP
Electrical	12 W, 90-250V 50/60Hz	EMI/RFI	Complies with FCC Part 15, Class A, CE, EU, EMC, C-tick
Power	5 DC 3A	Size	171 mm W x 120 mm D x 44.45 mm H
Mount	Magnetic		