

Apantac MiniDE-4 4 HDMI INPTS CMPCT MULTIVIEWER w/DVI/HDMI OUTPT

VIDEO INPUTS	4 DVI / VGA / HDMI / YPbPr / Composite	OUTPUTS	1 DVI, HDMI
TOTAL WINDOWS	4	OUTPUT RESOLUTION	800 x 480 - 1920 x 1080 (1080p)
CONNECTORS	DVI-I (DVI-I-VGA Adapter DVI-I-Composite Adapter Optional DVI-IHDMI Adapter Optional DVI-I-YPbPr Adapter) BNC IEC 61169-8 Annex A	BUILT-IN-EXTENDER	Up to 35 feet Extend up to 115 feet (option)
COMPOSITE	NTSC (SMPTE-170M), PAL (ITU624-2)	ON-SCREEN DISPLAY	Labels Borders
SIGNAL LEVEL	1V nominal	GENERAL PURPOSE IO	40 inputs with DB9 connectors
DC OFFSET	0V, + - 0.1V	IP	100 Base-TX, Supported Protocols: TSL, AXP, Connector: RJ45
IMPEDENCE	75 ohm	ELECTRICAL	110W , 90-250V 50/60 Hz
RETURN LOSS	40db up to 5MHz	EMI/RFI	Complies with FCC Part 15, Class A, CE, EU EMC, C-tick
SIZE	Compact	POWER	Optional redundant power supply
CONTROL	Front panel buttons for quick preset recalls, GPIs, Apantac ASCII Protocol (AXP), Director (config & control app)		