

## Apantac Mx-32 Cost-Effective 32x4 Video Multiviewer

<b>VIDEO INPUTS</b>	32 3G Level A&B, HD/SD-SDI	<b>VIDEO OUTPUTS</b>	4 independent sets of HDMI, SDI outputs
<b>CONNECTOR TYPE</b>	BNC IEC 61169-8 Annex A	<b>AUDIO OUTPUTS</b>	Embedded HDMI and SDI out
<b>TOTAL WINDOWS</b>	Maximum of 128 windows	<b>OUTPUT RESOLUTION</b>	1920 x 1080p 50/60Hz
<b>SERIAL DIGITAL</b>	SMPTE 424M, 292M, 259M	<b>ON-SCREEN DISPLAY</b>	Borders, labels, tally UMD, OMD, IMD, dynamic UMD
<b>EQUALIZATION</b>	120m at 2.97 Gbps, 140m at 1.48 Gbps, 400m at 270 Mbps with Belden 1694A	<b>GENERAL PURPOSE I/O</b>	Up to 64 inputs with RJ50 - DB9 connectors
<b>RETURN LOSS</b>	> 15db up to 1.485 Gbps > 10db up to 3G	<b>SERIAL PORT</b>	Connector: RJ45, Baud Rate up to 115200 bps Protocol: TSL, TSI, AXP
<b>EMBEDDED AUDIO</b>	SMPTE-272M-A	<b>IP</b>	100 Base-Tx, TSL, AXP Connector: RJ45
<b>ALARMS</b>	No audio, audio high/low, no video, video format display	<b>ELECTRICAL</b>	75W, 90-250V 50/60 Hz
<b>EMI/RFI</b>	Complies with FCC Part 15 Class A, CE, EU EMC, C-tick	<b>POWER</b>	Redundant 90-250 AC
<b>SIZE</b>	2 RU, 48.5 cm (19")		