

# MC430-5-IP-P

## 4.3" 4MP 5-IN-1 TESTER TOUCH SCREEN



### Main Feature:

- 4.3" IPS touch screen
- 960\*540 resolution + new systems.
- H.265 video display via mainstream.
- RJ45 cable TDR test, cable quality test.
- DC 12V power voltage test, HDMI input, 1080P.
- TesterPlay: Tester, Android version mobile phone, PC display at the same time.
- Batch activate Hik camera.

### Specification:

Model	MC430-5-IP-P	
<b>LCD</b>		
Display	New 4.3" IPS touch screen, 960 x 540 resolution	
<b>Video Mode</b>		
CVBS	1CH BNC input & 1CH BNC looped out, NTSC/PAL (Auto adapt)	
	Analog video level meter, peak video signal level, SYNC signal level, color bar chroma level measurement	
	PTZ control, RS485/RS232 control, Baud 600-115200bps, compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, etc.	
	CVBS loop test. The tester send and receive color bar generator signal, check BNC cable	
IP Camera Test	8MP H.265 IPC test (ED Series) / IPC viewer / Rapid Video / RTSP / ONVIF	
	Rapid Video	Auto view the video, create testing report
	Hik test tool	pressing just one key to activate Hik camera, image test, can modify the user name, password and IP parameters
	DH test tool	DH camera test, modify the user name, password and IP parameters
IP & CVBS test	IP & CVBS test at the same time, converter test from analog to digital with dual test window	
Coaxial HD test	SMP TVI camera test, 2560 x 1944P, 12.5fps, UTC control / call OSD menu	
	4MP CVI camera test, 2560 x 1440P, 25/30fps, UTC control / call OSD menu	
	SMP AHD test, 2560 x 1944P, 15/25/30fps, UTC control / call OSD menu	
	HD-SDI/EX-SDI not supports	
HDMI Input	1CH HDMI input, support 1080P, 1080I	
Zoom Image	4X zoom, to enlarge image, screen snapshot, record, save, view, and record and playback	
<b>Video Out</b>		
Analog Output	Color bar generator: Output 1CH PAL/NTSC color bar video signal for testing monitor or video cable	
HDMI Output	1CH HDMI output, support 1920 x 1080P	
<b>Power Output</b>		
12V / 2A power	Output DC 12V / 2A power out, supply temporarily power for the camera	
PoE power output	48V PoE power output, max power 24W	
5V / 2A power output	USB 5V 2A power output, as a power bank	
<b>Cable Test</b>		
TDR Cable Test	BNC cable, network cable, telephone cable, RVV cable and elevator cable, Cat5/6 Cable's length and short circuit. Measurement range 1.2KM	
Cable Tracer	Search BNC cable, network cable and telephone cable from the mess cables	
UTP Cable Test	Test UTP cable connection status and display on the screen. Read the number on the screen	
RJ45 Cable TDR Test	Test cable pair status, length, attenuation, reflectivity, impedance, skew, etc.	
<b>Others</b>		
Tester Play	Screen projection: tester, mobile phone and PC display at the same time (For Android version mobile phone)	
Network Test	Trace route, Link monitor, DHCP server, Port flashing, Ping test	
Wi-Fi	Built-in Wi-Fi, speeds 150M, display wireless camera image	
Audio Test	1CH audio signal input, test whether sound normal, 1CH audio signal, to connect headphone	
Data Monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal	
PoE Test	Measurement PoE Switch or PSE power supply voltage and cable connection status	

Design and specifications are subject to change without notice.

www.EasternCCTV.com

#### Headquarters

50 Commercial St.,  
Plainview, NY 11803

TEL: 516-870-3779 FAX: 516-390-1200

#### Queens, NY

129-04 14th Ave.,  
College Point, NY 11356

TEL: 718-939-2710 FAX: 718-939-2713

#### E. Los Angeles, CA

110 California Ave.,  
City of Industry, CA 91744

TEL: 626-961-8810 FAX: 626-961-8809

#### N. Hollywood, CA

13761 Saticoy St.  
Panorama City, CA 91402

TEL: 818-924-9021 FAX: 818-849-5127

#### Miami, FL

4515 NW 72nd Ave.  
Miami, FL 33166

TEL: 305-423-1329 FAX: 786-717-7282

#### Houston, TX

3790 Westchase Dr.,  
Houston, TX 77042

TEL: 832-308-5282 FAX: 832-925-7454